

Intercomp SWII™ Portable Racing Scales



Standard Features

- Display that shows any combination of wheel weights or percentages of weight: left side, wedge, etc.
- Easy to use automatic zero and keypad calibration
- High accuracy and repeatability
- Full 1-year warranty
- Units of measure: lb/kg
- Lightweight, low-profile weigh pads, 15" L x 15" W x 4" H
- Weigh pads have leveling feet and handles
- Large Liquid Crystal Display (LCD)
- Powered by six AA batteries

Specifications

GENERAL CONTROLS:

Zero, on, off, weight/%

CHANNEL SELECTION:

Left front (LF), right front (RF), left rear (LR), right rear (RR), All

WEIGHT & PERCENT:

Weight and percent selection

INDICATORS:

Lo bat, lb/kg

SPEED:

950 milliseconds to typical reading (static)

ACCURACY:

± 0.1% or 1 lb/0.5 kg

CALIBRATION:

Keypad calibration

UNITS OF MEASURE:

lb, kg selectable

VOLTAGE:

12VDC, 115/230 VAC

BATTERIES:

"AA" size rechargeable Ni-cad or alkaline

HUMIDITY:

10 to 95% non-condensing

TEMPERATURE:

Operating: 32°F to 122°F (0°C to 50°C)

Storage: -40°F to 170°F (-40°C to 75°C)

WEIGH PAD:

Overall dimensions:

15" L x 15" W x 4" H

Weight: 23 lb (10.5 kg)

Material: Aerospace grade cast aluminum

WARRANTY:

1-year limited warranty

DIMENSIONS

PART #	MODEL	WEIGH PAD SIZE	CAPACITY	GRADUATION	EST. SHIP WT
43688	SWII 4000	15" x 15" x 4"	4000 lb/1800 kg (1000 lb/450 kg/pad)	1 lb (0.5 kg)	105 lb (47.6 kg)
43689	SWII 6000	15" x 15" x 4"	6000 lb/2800 kg (1500 lb/700 kg/pad)	1 lb (0.5 kg)	105 lb (47.6 kg)